

LE ANSWER 2 OF 55 JAFIO COPYRIGHT 1999 JFO and Japic
AN 1994-062147 JAFIO
TI COMMUNICATION SYSTEM
IN HASEGAWA KAZUHIKO
FA MURATA MACH LTD, JF (CO 330342)
PI JP06062147 A 19940304 Heisei
AI JFI1992-216921 (JP04216921 Heisei) 19920814
SO PATENT ABSTRACTS OF JAPAN, Unexamined Applications, Section: E, Sect. No.
1559, Vol. 18, No. 3, P. 116 (19940610)
IC ICM (5) H04M011-00
ICS (5) H04M003-42; (5) H04N001-32
CC 44.4 COMMUNICATION - Telephone
36.4 LABOR SAVING - Service automation
44.7 COMMUNICATION - Facsimile
CT R131 INFORMATION PROCESSING - Microcomputer (Microprocessor)
AB PURPOSE: To provide a communication system which reports erroneous
incoming from the telephone set side to the facsimile side at the time of
erroneous incoming of facsimile communication to the telephone set.
CONSTITUTION: A telephone set 2 is provided with a ROM 38 where a program
of a nonstandard protocol which inserts a signal indicating erroneous
communication to a digital discrimination signal is stored, a modem 34
which transmits the former signal to the **facsimile** equipment of
the other party, and an **error** indicating button 42. The
facsimile equipment 1 is provided with a ROM 21 where a program
which receives and decodes the erroneous communication indicating signal
from the telephone set 2 to perform the processing like operator call is
stored. When an operator depresses the **error** indicating button
42 after hearing the voice signal from the **facsimile**, the
calling subscriber of the **facsimile** is immediately called
without unnecessary picture transmission and reception, and erroneous
incoming is directly reported with a voice. If any operators do not exist
on the **facsimile** side, the record is **left** as an
error message.